

SC9D310D2

Used for 200kVA generator



◎ POWER RATING

Engine Speed	Type of	Engine Power	
rpm	Operation	kW	Ps
1500	Prime Power	208	287
	Standby Power	228	310

-. The engine performance is as per GB/T2820.

-. Ratings are based on GB/T1147.1.

---Prime power is available for an unlimited number of hours per year in a variable load application. The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

---Standby power is available in the event of a utility power outage or under test conditions for up to 200 hours of operation per year.

The permissible average power output over 24 hours of operation shall not exceed 80% of the standby power rating.

◎ SPECIFICATIONS

◎ FUEL CONSUMPTION

○ Engine Model	SC9D310D2	○ Power	lit/hr
○ Engine Type	In-line,4 strokes, water-cooled	25%	13.9
	Turbo charged	50%	26.3
	air-to-air intercooled	75%	38.2
○ Combustion type	Direct injection	100%	50.6
○ Cylinder Type	Wet liner	110%	55.6
○ Number of cylinders	6		
○ Bore × stroke	114(4.49) × 144(5.67) mm(in.)		
○ Displacement	8.82(538.2) lit.(in3)		
○ Compression ratio	18 : 1		

○ Firing order
1-5-3-6-2-4

◎ FUEL SYSTEM

○ Injection timing	6°BTDC	○ Injection pump	Longkou in-line “P” type
○ Dry weight	Approx. 740kg (1631b)	○ Governor	Electric type
○ Dimension	1455×762×1273 mm	○ Feed pump	Mechanical type
(L×W×H)	(57.3×30.0×50.2 in.)	○ Injection nozzle	Multi hole type
○ Rotation	Counter clockwise viewed from Flywheel	○ Opening pressure	250 kg/cm2 (3556 psi)
		○ Fuel filter	Full flow, cartridge type

○ Fly wheel housing	SAE NO.2	○ Used fuel	Diesel fuel oil
○ Fly wheel	SAE NO.11.5		
◎ MECHANISM		◎ LUBRICATION SYSTEM	
○ Type	Over head valve	○ Lub. Method	Fully forced pressure feed type
○ Number of valve	Intake 1, exhaust 1 per cylinder	○ Oil pump	Gear type driven by crankshaft
○ Valve lashes at cold	Intake 0.30mm (0.0118 in.)	○ Oil filter	Full flow, cartridge type
	Exhaust 0.50mm (0.0197 in.)	○ Oil pan capacity	High level 19 liters (5.02 gal.) Low level 15 liters (3.96 gal.)
◎ VALVE TIMING		○ Angularity limit	Front down 25 deg. Front up 35 deg.
	Opening		Close
○ Intake valve	22.5 deg. BTDC		34.5 deg. ABDC
○ Exhaust valve	67.5 deg. BBDC		25.5 deg. ATDC
◎ COOLING SYSTEM		○ Lub. Oil	Refer to Operation Manual
◎ ENGINEERING DATA			
○ Cooling method	Fresh water forced circulation	○ Water flow	200 liters/min @1,500 rpm
○ Water capacity	12 liters (3.17 gal.)	○ Heat rejection to coolant	20.35 kcal/sec @1,500 rpm
(engine only)		○ Heat rejection to CAC	10.4 kcal/sec @1,500 rpm
○ Pressure system	Max. 0.5 kg/cm ² (7.11 psi)	○ Air flow	16.4 m ³ /min @1,500 rpm
○ Water pump	Centrifugal type driven by belt	○ Exhaust gas flow	35.9 m ³ /min @1,500 rpm
○ Water pump Capacity	200 liters (52.8 gal.)/min	○ Exhaust gas temp.	600 °C @1,500 rpm
	at 1,500 rpm (engine)	○ Max. permissible	
○ Thermostat	Wax–pellet type	restrictions	
	Opening temp. 82°C	Intake system	3 kPa initial 6 kPa final
	Full open temp. 93°C		
○ Cooling fan	Blower type, plastic	Exhaust system	6 kPa max.
	762 mm diameter, 10 blades	○ Max. permissible altitude	2,000 m
○ Cooling air flow	6.23 m ³ /s	○ Fan power	8 kW

◎
 ELECTRICAL SYSTEM

○ Charging generator	28V×55A
○ Voltage regulator	Built-in type IC regulator
○ Starting motor	24V×7.5kW
○ Battery Voltage	24V
○ Battery Capacity	180 AH

◆
 CONVERSION TABLE

in. = mm × 0.0394	lb/ft = N.m × 0.737
PS = kW × 1.3596	U.S. gal = lit. × 0.264
psi = kg/cm2 × 14.2233	kW = 0.2388 kcal/s
in ³ = lit. × 61.02	lb/PS.h = g/kW.h × 0.00162
hp = PS × 0.98635	cfm = m3/min × 35.336
lb = kg × 2.20462	

