



*Illustrative image

Powered by



Genset

Prime Power (kVA)	313
Standby Power (kVA)	344
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	455
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)*	51,8
Running Noise (db(A)@7m)*	75±3
Silent Type-Dimension (mm)*	4000x1150x2000
Fuel (L)*	450
Silent Type-Weight (kg)*	3200
Power factor	0,8

Control Panel System

Option:

Deepsea/Datakom/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	YCMK10TAA420-G20
Origin	China
Brand	Yuchai
Cylinder No. & Config	6L
Compression ratio	16.8:1
Output Power (kW)	281
Governor	Electronic
Coolant Capacity (L)	65
Oil Capacity (L)	30
Displacement (L)	10,34
Bore x Stroke	123x145
Air intake system	Turbocharged, air-air intercooled

Alternator

Brand Alternator	Stamford/ Mecc Alte/ Leroysoner/ Benzen Power
Rated Power (kVA)	313
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.